

COR-IP2SP20X

6 INCH NETWORK IR PTZ with 20x OPTICAL ZOOM



KEY FEATURES

- 1/2.8" Progressive Scan CMOS
- 30fps@1920*1080 ~ 30fps@320*240
- 20X Optical Zoom
- 72~ 3.8 degree (Wide~Tele) Angle of View
- WDR / Smart Defog / BLC / AGC
- H.264/H.265 Video Compression
- IR range 492 feet
- Proportional Zoom
- 255 PTZ Presets



20X
OPTICAL
ZOOM



SPECIFICATIONS

* CAMERA	
Resolution	1920x1080
Image Sensor	1/2.8" Progressive Scan CMOS
Signal System:	PAL / NTSC
Effective Pixels	1920x1080
Focal Length	F1.6 ~ F3.0 , 4.7mm -104mm
Lens	20X Optical Zoom
Angle of View	72~ 3.8 degree (Wide~Tele)
Minimum Illumination	AGC On: Color: 0.5 lux, B/W : 0.05 lux, 0 lux with IR
White balance	Auto,/ Manual / Indoor
AGC	Auto / Manual
BLC	On / Off
Smart Defog	Support
WDR	120db
Shutter time	1/5 - 1/20000
Day& Night:	IR cut filter with auto switch
* VIDEO	
Compression	Main Stream : H.264/H.265
Video Output	1 Output : CVBS (BNC Type)
Transmission	H.264 / H.265 Triple Streaming
Resolution	30fps@1920*1080 ~ 30fps@320*240
AUDIO	
Input	1 Line-in
Output	1 Line-out
* ALARM	
Input	1 input
Output	1 output

* NETWORK	
Ethernet	10/100Mbps ethernet interface
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
No.of Simultaneous Users	5 users
RS485 interface	Control by Joystick controller (Only used PTZ function)
* INFRARED	
IR irradiation distance	492 feet (150M)
IR Diming function	Adjustable by zoom
* PAN & TILT	
Pan Range	360°endless
Tilt Range	-10°~95° (Auto Flip)
Pan Speed	0.1~300°/sec
Tilt Speed	0.1~100°/sec
Proportional Zoom	Rotation speed can be adjusted automatically according to zoom multiples
Preset	255
Preset speed	Max.300°/sec
Tour	4 Tour / 8 preset each
Pattern	4 Patterns
Scan	1 Scans
Home position	Preset / Tour / Scan / Pattern
* GENERAL	
Power Supply	AC 24V
Working Temperature/ Humidity	-40°C ~ + 70°C (-40~+158°F) <90% (Outdoor)
Weight	Approx. 2kg (4.4 pounds)
Water Proof	IP66

